


## Series 8, Induction cooktop, 80 cm, surface mount with frame PXX875D67E



### Included accessories

1 x Slider for unducted recirculation  
1 x Clean Air Plus odor filter

### Optional accessories

HEZ32WA00 Wireless food thermometer, HEZ390011 Stainless Steel roaster with glass lid, HEZ39050 Wireless temperature sensor for cooktop, HEZ390522 Griddle Plate, HEZ9ES100 Espresso maker 4 cups, HEZ9FE280 Iron pan Ø 18 / 28 cm, HEZ9FF010 Flex Pan, large, HEZ9FF030 Flex Pan set, 3 pcs., HEZ9SE030 Set of 2 Pots and 1 Pan, HEZ9SE060 6 pieces Set, HEZ9VDKE1 Exhaust kit, HEZ9VDKR0 Recirculation kit 2 L-bow (70cm), HEZ9VDSB1 90° flat duct bend horizontal, HEZ9VDSB2 90° flat duct L vertical, HEZ9VDSB3 90° flat duct M vertical, HEZ9VDSB4 90° flat duct S vertical, HEZ9VDSI0 Adapter round-flat, HEZ9VDSI1 90° Adapter round-flat, HEZ9VDSM1 Straight tube 500mm, HEZ9VDSM2 Straight tube 1000mm, HEZ9VDSS1 Connector sleeve (female), HEZ9VDSS2 Flex sleeve (female), HEZ9VEDU0 Acoustics Filter, HEZ9VRPD1 Plinth Diffuser

## The induction cooktop with integrated ventilation module: combines the best induction with the best ventilation technology for perfect results.

- **Integrated ventilation:** extracts steam and cooking odours directly from the source.
- **FlexInduction:** combines two cooking zones into one large, even heating area for flexible cooking.
- **Power Boost:** up to 35% faster heating compared to highest power level.
- **PerfectFry sensor:** automatically regulates the pan temperature to prevent food from burning.
- **PerfectAir sensor:** automatically adjusts extraction for optimal performance with minimal noise.

### Technical Data

Product name/family : Cooking zone ceramic

Built-in / Free-standing : Built-in

Energy input : Electric

Total number of positions that can be used at the same time : 4

Required niche size for installation (HxWxD) : 223 x 750-750 x 490-490 mm

Width of the appliance : 816 mm

Dimensions : 223x816x527 mm

Dimensions of the packed product (HxWxD) : 430x940x660 mm

Net weight : 28.7 kg

Gross weight : 33.4 kg

Residual heat indicator : Separate

Location of control panel : Front

Basic surface material : Ceramic

Color of surface : Black, Stainless steel

Color of frame : Stainless steel

Length electrical supply cord : 110 cm

Sealed Burners : No

heating with booster : All

Power of 2nd heating element (kW) : 3300.0 W

Number of speed settings : 17-stage + 2 intensive

Maximum output air extraction : 500 m³/h

Boost position output recirculating : 595.0 m³/h

Maximum output recirculating air : 499 m³/h

Boost position air extraction : 622 m³/h

Noise level : 69 dB(A) re 1pW

Odour filter : No

Operating Mode : Convertible

Clean filter reminders : Yes

Voltage : 220-240/380-415 V

Frequency : 50-60 Hz

Main colour of product : Black

Included accessories : 1 x Slider for unducted recirculation, 1 x Clean Air Plus odor filter



4 242005 192540

## Series 8, Induction cooktop, 80 cm, surface mount with frame PXX875D67E

**The induction cooktop with integrated ventilation module: combines the best induction with the best ventilation technology for perfect results.**

### Design

- Stainless steel side trims with bevelled front.
- Cooking zones will be automatically joined or separated based on the shape and size of the cookware placed.

### Integrated ventilation downdraft system

- 17 electronically controlled fan power levels and 2 intensive fan power levels  
Sensor-based, smart, fully automatic ventilation system  
Automatic switch-on of ventilation system when a cooking zone is used  
Sensor-based and cooktop-based, fully-automatic adjustment of power levels  
3 ventilation modes: Low-noise, balanced, performance mode.  
Automatic delayed shut-off after cooking to remove residual odors after cooking  
Manual control of the fan level is possible at any time
- Saturation indication for CleanAir odor filters via user interface notification.
- Extraction rate according to EN 61591:  
Ducted extraction (Min/Max/Intensive): 154/500/622m<sup>3</sup>/h  
Recirculated extraction (Min/Max/Intensive): 132/499/595 m<sup>3</sup>/h
- High performance grease filter and liquid collector unit  
Convenient one-hand removal via floating glass ceramics handle  
Easy-to-clean, fully dishwasher safe and heat resistant  
Upper and lower liquid collector units accidental spillage, overall capturing capacity of 900ml (upper 200ml + lower 700ml)  
Watertight blower system

### Planning & installation notes

- To complete the fully ducted extraction or to do any other individual recirculation planning additional ducting accessories are required.  
Note: BSH vented cooktops and/or hoods can in some applications be installed in recirculation mode, consideration of the conditions of the NZ regulations must be undertaken prior to purchase/installation, we recommend getting qualified advice from an air-movement/ventilation specialist to either design a suitable ventilation design or determine whether the design you are undertaking will comply with NZ regulations.  
BSH are not installation experts and cannot provide any further information on this topic. If the installer/purchaser chooses to install the product in recirculation mode, then it is up to the installer/purchaser to determine how to ensure their design complies with the NZ regulations.  
BSH are unable to provide additional assistance if the installation is deemed non-compliant.

### Flexibility of cooking zones

- 2 FlexZones: use cookware of any shape or size anywhere within the 40cm cooking zone.
- Cooking zone front left: 200 mm, 240 mm, 2.2 KW (max. power 3.7 KW)
- Cooking zone rear left: 200 mm, 240 mm, 2.2 KW (max. power 3.7 KW)
- Cooking zone rear right: 200 mm, 240 mm, 2.2 KW (max. power 3.7 KW)
- Cooking zone front right: 200 mm, 240 mm, 2.2 KW (max. power 3.7 KW)

### Comfort & Convenience

- Direct Select 2.0: directly control the power on the extra large illuminated touch bar (invisible when switched off).
- 17 power levels: precisely adapt the heat with 17 power levels (9 main levels and 8 intermediate levels).
- Keep warm function: keep dishes warm at preset low power level.
- Timer with automatic switch off for all zones: switches off the cooking zone at the end of the time set (e.g. for boiled eggs).
- Count-down timer  
: an alarm sounds at the end of the time set (e.g. for pasta).
- Timer / Alarm clock: shows how much time has passed since starting the timer (e.g. for potatoes).

### Time saving & Efficiency

- PowerBoost function - reduce the time to heat up large quantities of water: boil water faster with up to 50% more power than at the highest standard level.
- PanBoost: heat up pans more quickly than at the highest standard level while protecting the pan coating.
- 3-steps: increase or decrease the power level simply by moving the pot forwards or backwards.
- Automatic Setting Transfer: when moving a pot to a different cooking zone (Flex zone), transfer all previous settings to the new zone at the touch of a button.
- QuickStart: Quick and automatic first pot detection: when switching on, the cooktop automatically selects the cooking zone with cookware on it.
- ReStart function: in case of unintentional switch-off, restore all previous settings by switching on the cooktop again within 4 seconds.

### Connectivity

- HomeConnect enabled: check if the cooktop is switched off even when not at home, and find recipes or additional functions in the Home Connect app. [www.home-connect.co.nz](http://www.home-connect.co.nz)

### **Safety**


- Digital 2 stage residual heat indicator: indicates which cooking zones are still hot or warm.
- Childproof lock: prevent unintended activation of the cooktop.
- demo mode, WipeProtection, Childproof lock, overflow protection, PowerManagement Function, Automatic pan recognition sensor, Automatic Safety switch-off: wipe overboiled liquids without unintentionally changing settings (blocking all touch buttons for 30 seconds).
- Main switch: switch off all cooking zones at the touch of a button.
- Automatic Safety switch-off: for safety reasons, heating stops after a preset time without interaction.
- Energy consumption: shows the electricity consumption of the last cooking process.

### **Installation**



- Dimensions of the product (HxWxD mm): 223 x 816 x 527
- Required niche size for installation (HxWxD mm) : 223 x 750 x (490 - 490)
- Min. worktop thickness: 16 mm
- Connected load: 7.4 KW
- PowerManagement Function: enables the total power of the cooktop to be limited if necessary (for suitability and installation, consult a licensed electrician).

## Series 8, Induction cooktop, 80 cm, surface mount with frame




### PXX875D67E








A	E	F	G	H
S-size	≥ 600	547	545	579
M-size	≥ 650	574	569	603




A: Adapter round-flat



## Series 8, Induction cooktop, 80 cm, surface mount with frame PXX875D67E




measurements in mm  
Front view – unit cut-out  
for unducted recirculation




A: Minimum distance from the hob cut-out to the wall

## Series 8, Induction cooktop, 80 cm, surface mount with frame PXX875D67E


measurements in mm  
Front view



measurements in mm




measurements in mm  
Front view




A: Connected directly at the rear

measurements in mm



- A:** Recess depth  
**B:** Cut-out in back panel required for pipework. Exact size and position can be taken from specific drawing.  
**C:** All 80 cm width class models can be installed in 60 cm wide furniture by adjusting the side panels.

Measurements in mm



measurements in mm

